



Gängmaskiner



Fiam MAY 12 P

Art. nr	Modell	Varvtal	Slangdim. Inv	Kapacitet	Luftförbr.	Ljudtrycks- nivå	Vikt
		rpm	mm		liter/s	dB	kg
320-Ö5	MAS 8 P	500/800	8	M8	10		1,04
320-Ö3	MAY 12 P	250/470	8	M12	12	78	1,96

Maskinerna är utrustade med snabbväxelchuck.

Tapphållare:

Art.nr.	Dimension	Art.nr.	Dimension
832-N1	2,8/4-k. 2,1 mm, 655211028	832-P1	7,0/4-k. 5,5 mm, 655551070
832-N2	3,0/4-k. 2,4 mm, 655241030	832-P2	7,3/4-k. 5,5 mm, 655551073
832-N3	3,5/4-k. 2,7 mm, 655271035	832-P3	8,0/4-k. 6,2 mm, 655621080
832-N4	4,0/4-k. 3,0 mm, 655301040	832-P4	8,5/4-k. 7,0 mm, 655701085
832-N5	4,5/4-k. 3,4 mm, 655341045	832-P5	9,0/4-k. 7,0 mm, 655701090
832-N6	5,0/4-k. 3,8 mm, 655381050	832-P6	9,4/4-k. 7,0 mm, 655701094
832-N7	6,0/4-k. 4,9 mm, 655491060	832-P7	10/4-k. 8,0 mm, 655801101
832-N8	6,3/4-k. 5,0 mm, 655501062	832-P8	11/4-k. 9,0 mm, 655901110
832-N9	6,5/4-k. 4,9 mm, 655491065	832-P9	12,0/4-k. 9,0 mm, 655911121
		832-R3	12,5/4-k. 10 mm, 655901112