Chicago Pneumatic



15% SMALLER than any other butterfly impacts. Compact & lightweight!

1338:-

CP7711 1/4"

Art nr 8941077110 CP7721 3/8"

Art nr 8941077210

- ✓ Power regulator in the back: 3 positions on both sides
- ✓ Butterfly shift for forward / reverse
- ✔ Built-in 180° air inlet swivel
- ✓ Max torque (rev) 110 Nm
- ✓ Length: 140 mm
- ✓ Weight : 1,1 kg



Ultra Lightweight, Easy operation and Compact

1427:-

CP7732C 1/2"

Art nr 8941077321

- ✓ Max torque (rev): 625 Nm
- ✓ One hand operation forw rev
- ✓ 3 setting positions
- ✓ Length: 108 mm
- Jumbo Hammer
- ✓ Weight: 1,0 kg

VEHICLE SERVICE

SPECIAL OFFER AUTUMN 2016

People. Passion. Performance.



Impact wrenches



BENEFITS

- ✓ 3 positions in fwd and 1 in rev
- ✓ Suited for all maintenance applications
 - Light vehicles tire changing operations
 - Light vehicles mechanical repair
 - MRO applications
- ✓ Well balanced minimizing wrist strain
- ✓ Ergonomic handle fits perfectly in the hand
- ✓ Twin hammer mechanism and steel motor
- ✓ Length: 192 mm
- ✓ Weight: 2.6 kg

BENEFITS

- ✓ 1250 Nm of maximum torque in reverse
- ✓ 3 positions in fwd 245, 650, 990 Nm.
- Most powerful tool on the market in its class: 1250 Nm of maximum real torque in reverse
- Lightweight due to composite housing
- ✓ Contoured comfort grip handle instead of TPR injected in handle
- ✓ Smooth Forward / Reverse Switch on back
- Twin hammer mechanism
- ✓ Length: 200 mm
- ✓ Weight: 2.0 kg



Art nr 8941077480



BENEFITS

- ✓ 1300 Nm maximum real torque in reverse
- ✓ 1 hand-operation behind the trigger
- 2 positions in reverse: max and lower torque
- 2 position in forward: max and low torque
- ✓ Curved handle with Thermo-Plastic Rubber injected in housing for a durable and comfortable grip
- ✔ Aluminum alloy front housing
- ✓ Composite housing
- ✓ Twin Hammer mechanism
- ✓ Length: 171 mm
- ✓ Weight : 1,8 kg





Thin wall wheel protection **SS413WP** Art nr 8940164464

Art nr 8940164464

½"• 17,19 & 21 mm.....**219:**-

414WP Art nr 8940168375 ½"• 17,19,21 & 22 mm......**290:**-

13DTW Art nr 8940166760

½"• 17,19 & 21 mm.....**219:**-

Impact wrenches



BENEFITS

- ✔ Powerful impact for General Maintenance
- ✓ Maximize operator comfort: lightweight and balanced design
- ✓ S2S easy forward reverse
- ✓ 1950 Nm of maximum torque in reverse
- ∠ Length: 214 mm
- ✓ Weight : 3,4 kg

4999:-

CP7769

BENEFITS

balanced design ✓ S2S easy forward reverse

✓ Length: 214 mm ✓ Weight : 3,5 kg

✔ Powerful impact for General Maintenance ✓ Maximize operator comfort: lightweight and

√ 1950 Nm of maximum torque in reverse

8941077690







GP7779

8941077790

ht & Compact



BENEFITS

- ✓ 2600 Nm of maximum torque in reverse
- ✓ High efficiency motor, yet economical with durable reinforced clutch mechanism
- ✓ Lenght: 520 mm
- ✓ Weight : 11,6 kg

5290:-





CP5000

rt nr T024585

Our strongest and most powerful 1" impact with an 7" extended anvil

BENEFITS

- ✓ Ideal for high volume tire work on trucks, buses, and heavy equipment
- ✓ Lenght: 572 mm
- ✓ Weight : 16,2 kg

12143:-



Pneumatic tools



BENEFITS

- ✓ Ratchets for general maintenance, durability and comfort
- √ 1/2" high power club ratche
- ✓ Highest torque on the market: 122 Nm
- ✓ Length: 305 mm
- ✓ Weight : 1,2 kg

2300:-

6151919426

BENEFITS

1/4" mini ratchet · 35 Nm Most powerful of its class Compact and lightweight Free speed: 270 rpm Length: 128 mm Weight: 0,7 kg

999:-

3/8" mini ratchet · 35 Nm Most powerful of its class Compact and lightweight Free speed: 270 rpm

Length: 128 mm Weight: 0,49 kg

999:-



6151919427



Art nr 6151952105 6151952105

BENEFITS

- ✓ Advanced motor and head design
- ✓ Better access to restricted areas
- ✓ Free speed: 225 rpm
- ✓ Max torque 95 Nm
- ✓ Length: 272 mm
- ✓ Weight : 1,24 kg

1650:-



T023995

699:-

BENEFITS

- √ 1/4" and 6 mm collets
- ✓ Ideal for limited space applications
- ✓ Free speed: 22500 rpm
- ✔ Power: 220 W
- ✓ Length: 124 mm
- ✓ Weight : 0,45 kg



CP9105Q-B

6151952105

▶ Power: 240 W

✓ Free speed: 28000 rpm

✓ Length & Weight: 160 mm 0,4 kg

799:-

CP9108Q-B

6151952108

▶ Power: 240 W

✓ Free speed: 28000 rpm

✓ Length & Weight: 200 mm 0,5 kg

947:-

CP9110Q-BArt nr 6151952110

✔ Power: 240 W

✓ Free speed: 25000 rpm

✓ Length & Weight: 260 mm 0,7 kg

883:-

All Grinders inludes 1/4" and 6 mm collets

Pneumatic tools





✓ Compact low profile head

✓ Chuck capacity: 10 mm

✓ Free speed: 1800 rpm

▶ Power: 200 W

BENEFITS

✓ Weight: 1,02 kg

1100:-

1595:-6151949789

BENEFITS

✔ Powerful and resistant to stalls in general maintenance applications

✓ Chuck capacity: 13 mm

✓ Free speed: 800 rpm

✔ Power: 270 W

✓ Weight: 1,42 - 1,80 kg

1552:-

6151949791

BENEFITS

✓ Excellent for paint removal, weld sanding, smoothing and rust removal in tight area

✔ Paper size 10x330

✓ Free speed: 22000 rpm

✓ Power: 260 W

✓ Weight: 0,90 kg

6151939779

1571:-



BENEFITS

✔ Reduced vibration for operator comfort and control

✓ Strokes per minute10000

✓ Stroke: 10 mm

✓ Net weight: 0.86 kg

✓ Length: 229 mm

1412:-



18 TEETH · Art nr 8940158775

24 TEETH · Art nr 8940158776

32 TEETH · Art nr 8940158777

100:-





TORQUE WRENCHES

MODEL	PART NUMBER	SQ DRIVE	CAPACITY Nm	GRADUATION Nm	LENGTH mm	WEIGHT kg	PRICE
CP8905	8941089050	1/4"	5-25	0,1	245	1,28	1363:-
CP8910	8941089100	3/8"	20-100	0,5	410	1,50	1363:-
CP8915	8941089150	1/2"	40-200	1,0	520	2,02	1400:-
CP8920	8941089200	3/4"	150-750	5,0	1060	16,20	5280:-
CP8925	8941089250	1"	200-1000	5,0	1255	16,20	6619:-

MODEL	PART NUMBER	LENGTH	LIFTING CA	APACITY	PRICE
		mm	ton	mm	
CP80015	8941081015	920	1.5	540	2999:-
CP80020	8941181020	750	2.0	505	2490:-
CP80030	8941181030	779	3.0	550	3200:-



MODEL	PART NUMBER	CAPACITY	PRESS HIGHT		PRICE
		tons	mm min.	mm max.	
CP86200	8941086200	20	185	1175	7999:-
CP86300	8941086300	30	151	1031	13999:-
CP86750	8941086750	75	170	884	29999:-

MODEL	PART NUMBER	CAPACITY (kg)	MIN HIGHT (mm)	MAX HIGHT (mm)	MAX FORK WITH (mm)	PRICE
CP87700	8941087700	700	905	1430	685	7999 :-
CP87120	8941087120	1200	1360	2110	1510	12895:-

Accessories



HOSE REELS



- Extreme Robustness
- Made for All Purposes
- Adapted even to Industrial Uses



- Open
- More adapted to dirty environments
- Still Great Robustness and For All Purposes



PIC. REF	DESCRIPTION	PART NUMBER	THREAD	HOSE LENGTH (m)	Ø INT. (mm)	MATERIAL	PRICE
Α	BSP HR8108	8940171991	1/4"	10	8	Composite	1599:-
Α	BSP HR8208	8940171995	1/4"	10	8	Aluminum	1976:-
Α	BSP HR8110	8940171993	1/4"	16	10	Composite	2290:-
Α	BSP HR8210	8940171997	1/4"	16	10	Aluminum	2975:-
В	BSP HR9110	8940172001	3/8"	21	10	Composite	4296:-
Α	BSP HR8113	8940171999	1/2"	16	13	Composite	3298:-
В	BSP HR9113	8940172003	1/2"	16	13	Composite	4590:-

AIR FLEX

Aimed to improve the working ergonomy, Air flex connectors can rotate 360° eliminating efforts when working in cramped spaces



MODEL	PART NUMBER	RECOMMENDED FLOW - MAX	PRICE
		l/s	
1/4"	894 017 1568	12	450:-
3/8"	894 017 1570	35	599:-
1/2"	894 017 1566	35	599:-

SWIVEL



Aimed to improve the working ergonomy, Air flex connectors can rotate 360° eliminating efforts when working in cramped spaces.

MODEL	PART NUMBER	PRICE
SWIVEL	894 015 8412	146:-



OIL AND GLOVES

DESCRIPTION	PART NUMBER	PRICE
Air Tool Oil - 120 ml	CA149661	26:-
CP Gloves L	8940158618	299:-
CP Gloves XL	8940158619	299:-

BLOW GUN





COUPLINGS AND FILTERS, REGULATORS, LUBRICATORS (FRL) – CHECK OUR MAIN CATALOG



Regulator adjusting knob

1/4", 3/8" and 1/2" NPT and BSP sizes

Protect gauge Always on the right position

Aluminium body



Oil adjustment

Oil fill plug

Bowl guard with integral plastic bowl

Semi automatic drain



Easily find the tools you need to get the job done!



CP ToolBox







Get the free CP ToolBox Scan this QR code or visit www.cp.com/app



ORDER DIREKT: order@mk-produkter.se

MK-Produkter AB

Box 8, 183 21 Täby
Tel: 08-514 00 550
Email: info@mk-produkter.se •
order@mk-produkter.se



