





### CP7755 Air Flex Mini

### 1/2" Impact Wrench

 360° rotatable air connection (Air-Flex-Mini) integrated and multiaxial

- Good accessibility, easy handling
- 1300 Nm. max. reverse torque
- Twin hammer mechanism
- Only 169mm long
- Specially designed and rubberized case for the daily use in theworkshop
- · Friction ring socket retainer
- 11 torque settings so you always have the torque you need
- 5,10,15,20,25,30,35,40,45,50 and 100% of maximum torque

3300:-Art.-Nr.: 8941077551

**Patented** 

multiaxial

swiveling

(Air Flex Mini)

air connection



# 1/2" Impact Wrench

- The new series of Chicago Pneumatic CP7741 air impact wrenches combines the highest quality and an attractive price
- Weighing just 2.25 kg, the CP7741 impact wrench (short spindle) is 15 percent lighter than the previous model and is therefore even easier to handle
- The composite housing offers optimal ease of use with significantly less heat transfer between the motor and the handle



**1750:-**Art.-Nr.: 8941077410

## www.cp.com/nordic

# Our complete assortment online:

- Online Catalog Pneumatic Tools
- Online workshop equipment catalogue
- CP accessories
- Technical documentation
- · CP sales and dealer contacts





# **MAINTENANCE AND SERVICE**

### CP7160 / CP7165

### **Airhammer Kits**

- Robust chisel hammers with built-in air suspension (reduces vibrations)
- Quick change chuck foreasy change of Chisel included
- · Contains:
- Tool (CP7160 or CP7165)
- A quick change retainer
- A spring retainer
- A mini oiler
- A Chicago Pneumatic soft bag
- 5 chisels



### **CP7901**

### Air reciprocating saw

- Premium tool for all cutting applications
- Low Vibrations
- Great power and speed of 10,000 strokes per minute
- Stroke: 10mm
- · 360° swivel air inlet
- · Net weight: 0,86kg



### CP7160K

### **CP7165K**

**2450:-**Art.-Nr.: 8941071601

2600:-Art.-Nr.: 8941071651

### CP9792C

### **Keyless Drill**

- 10 mm Chuck
- High ergonomiccomfort and optimal control
- · User-friendly
- Speed: 2100 rpm
- Torque: 5 1/2 Nm
- High quality industrial Jacobs® drill chuck
- · Right/left rotation



1499:-Art.-Nr.: 8941097920

### **CP72XXCVE**

### Orbital Palm Sanders, 2.5-10mm

- · Powerful and easy to use for vertical and horizontal applications
- · Shut-off and speed control switch
- 3 variations for different applications:
- CP7225CVE: 8941272253, 2.5 mm: used for final sanding
- CP7255CVE: 8941272553, 5 mm: great for surface preparation
- CP7215CVE: 8941272153, 10 mm: great for heavy material removal



2100:-For all CP72XXCVE

# **CP74 SERIES**

SEE THE CP74 SERIES IN ACTION!

Watch the video on YouTube





# 6 mm and 1/4» Air die grinder













Modell	CP7405	CP7406	CP7408	CP7410	CP7411	CP7412
Article no.	8941074050	8941074060	8941074080	8941074100	8941074110	8941074120
Collet size	1/4" and 6 mm	1/4" and 6 mm				
Power	250 W	250 W				
Free speed	28.000 Rpm	23.000 Rpm	23.000 Rpm	27.000 Rpm	22.000 Rpm	22.000 Rpm
Weight	0,5 kg	0,6 kg	0,62 kg	0,65 kg	0,7 kg	1,1 kg
Air requirement at maximum speed	1,3 [l/s]/ 9 [Nl/s]	1,7 [l/s]/ 12,1 [Nl/s]	1,7 [l/s]/ 12,1 [Nl/s]			
Minimum hose size	10 mm	10 mm				
Size air inlet thread	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"
Sound pressure	76,2 dB(A)	78,1 dB(A)	78,6 dB(A)	76,1 dB(A)	80,7 dB(A)	80,4 dB(A)
Sound power	87,2 dB(A)	89,1 dB(A)	89,6 dB(A)	87,1 dB(A)	91,7 dB(A)	91,4 dB(A)
Vibrations [m/s² – k]	3,60 - k = 0,98	5,40 - k = 1,27	4,30 - k = 0,93	4,90 - k = 0,96	3,10 - k = 0,79	2,60 - k = 0,76
Pricew	1340:	1499:-	1499:-	1390:-	2195:-	3850:-

# **TIRE SERVICE**

8941077550







Ove	rview	
Air	<b>Impact</b>	Wrenches

Modell	CP7755	CP7748	CP7748-2	CP7748TL
Article no.	8941077550	8941077481	8941077486	8941077487
Square drive	1/2"	1/2	2""	1/2"
Max Torque (Reverse)	1.300 Nm	1.300	) Nm	1.300 Nm
Working torque range (forward)	80 - 575 Nm	95 - 75	50 Nm	90 - 140 Nm
Free speed	7.700 rpm	7.000 rpm		7.000 rpm
Average air consumption	1,8 l/s	3 l/s		3 l/s
Clutch Type	Twin-Hammer	Twin-Hammer		Twin-Hammer
Air Inlet Thread Size	1/4"	1/4"		1/4"
Noise level	94 dB(A)	94,3 dB(A)		94.3 dB(A)
Net weight	1,85 kg	2 kg	2,11 kg	2 kg
Vibration	8,5 m/s²	12 m/s <sup>2</sup>	11,3 m/s <sup>2</sup>	12 m/s²

### **CP8915**

### 1/2" Torque Wrench, 40-200 Nm

- · Ideal for cars, motorcycles, quads and for engine and transmission maintenance
- Accuracy: 4% according to EN ISO 6789:2003
- Torque: 40-200Nm
- · Length: 495mm
- · Weight: 1.57kg

1,870:-Art.-Nr.: 8941089150





### 1/2" Torque Wrench, 60-340 Nm

- · Ideal for cars, motorcycles, guads and for engine and transmission maintenance
- Accuracy: 4% according to EN ISO 6789:2003
- Torque: 60-340 Nm
- · Length: 610mm
- Weight: 1.76kg

1980:-Art.-Nr.: 8941089170







2140:-CP7829H/CP7829

### **Our 1/2" Recommendations** For tight workspaces

Modell	CP7732C	CP7749	CP7749-2	CP7829H	CP7829
Article no.	8941077321	8941077491	8941077493	8941078294	8941078293
Square drive	1/2"		1/2"	1/2"	3/8"
Max Torque (Reverse)	625 Nm	13	800 Nm	95 N	lm
Working torque range (forward)	70 - 387 Nm	135	- 704 Nm	15 - 68	3 Nm
Free speed	9.410 rpm	7.0	000 rpm	225 ו	rpm
Average air consumption	2,6 l/s		3 l/s	5,2	l/s
Clutch Type	Jumbo	J	umbo	Jum	bo
Air Inlet Thread Size	1/4"	1/4"		1/4"	
Noise level	95,5 dB(A)	93 dB(A)	95 dB(A)	93 dE	3(A)
Net weight	1 kg	1,8 kg	2 kg	1,2	kg
Vibration	10,8 m/s <sup>2</sup>	10	,9 m/s <sup>2</sup>	10,3	m/s²











7300:-Art.-Nr.: 8941077820 7300:-Art.-Nr.: 8941077827


CP7763	CP7769	CP7779	CP7782	CP7782TL-6
8941077630	8941077691	8941077791	8941077820	8941077827
3/4"	3/4"	1"	1"	1"
1.630 Nm	1.95	60 Nm	2.600 Nm	2.600 Nm
136 - 1288 N.m	407 - 1	.464 Nm	500 - 2.000 Nm	400 - 440 Nm
6.300 rpm	6.50	0 rpm	5.200 rpm	5.200 rpm
3.5 l/s	4,8 l/s		4,8 l/s	4,8 l/s
Twin-Hammer	Twin-Hammer		Twin-Hammer	Twin-Hammer
3/8 "	3	/8"	1/2"	1/2"
96 dB(A)	96,8 dB(A)		100 dB(A)	100 dB(A)
5.25 kg	3,15 kg		10.1 kg	11,6 kg
10.4 m/s²	12,97 m/s²		7,8 m/s²	7,8 m/s²

### **CP8920**

### 3/4" Torque Wrench, 150-750 Nm

- · Ideal for small and medium-sized trucks
- Accuracy: 4% according to EN ISO 6789:2003
- Torque: 150-750 NmLength: 1,060 cmWeight: 16.2 kg

6750:-Art.-Nr.: 8941089200



### **CP8925**

# 1" Torque Wrench, 200-1.000 Nm

- Ideal for large trucks, buses,
- · construction machinery and agriculture
- Accuracy: 4% according to EN ISO 6789:2003
- Torque: 200-1,000 Nm
- Length: 1,255mm
- Weight: 16.2 kg

8350:-Art.-Nr.: 8941089250

### **CP Socket sets**



Large selection, available as a set or individually. imperial and metric, short and standard.

For 3/8», 1/2», 3/4», 1», from 7 to 70 mm.

### SS413WP 1/2" Socket set

Kit of 3: 17, 19 & 21mm. Art.-Nr.: 8940164464

250:-

### SS414WP 1/2" Socket set

**Kit of 4: 17, 19, 21 & 22mm.** Art.-Nr.: 8940168375

350:-

### SS4114D 1/2" Socket set

**Kit of 14: 10-19,21,22,26&27 mm** Art.-Nr.: 8940164459

875:-

### SS413DTW 1/2" Socket set

Kit of 3: 17, 19 & 21mm. Art.-Nr.: 8940166760 199:-

### SS618D 3/4" Socket set

Kit of 8: 26,27,29,30,32,35,36 & 38 mm Art.-Nr.: 8940164473

1500:-

### SS814D 3/4" Socket set

Kit of 4: 27, 32, 33 & 36 mm Art.-Nr.: 8940166016 1300:-

You can find more information in our accessories catalogue: http://qr.cp.com/sockets-brochure

### Lubrication

# Protection and Care For your tools

The appropriate care of pneumatic tools is key to ensure productivity, meet clients' demands and operators' safety.

### CPA1015 Air Tool Oil 125ml

Art.-Nr.: 8940176598

95:-

### **Grease Gun**

Art.-Nr.: C098689

235:-



### **CP800-Series**

### Trolley Jacks, 1.5t, 2t & 3t

- · Low profile and high load capacity
- 1,5,2 and 3 tons lifting capacity
- · Lifting height up to 505 mm
- · Welded steel chassis with reinforced edges
- · Hand pump and foot pedal for quick approach without load
- Handle with protective pad and soft rubber pad on saddle plate
- · Easy release of the load by turning handle
- · Low profile construction



### **CP81120**

### **Bottle Jack 12 t**

- · Large base plate for good standing and stability
- Double guide and chrome-plated steel piston in one piece, resulting in maximum load capacity and durability
- Automatically welded construction for 100% tightness, robustness and easy disassembly
- Thread extension in the piston for fast and easy height adjustment
- · Safety valve to protect against overload






### **CP820-Series**

Jack Stands 2t, 3t, 6t

Support stand made of ductile iron and robust steel skeleton construction



· Positions in height: 10

· Delivery in pairs

CP82030	CP82060				
8941082030	8941082060				
3t	6t				
455 mm	620 mm				
200	400				

Model	CP82020	CP82030	CP82060
Article no.	8941082020	8941082030	8941082060
Capacity	2t	3t	6t
Max Height	425 mm	455 mm	620 mm
Min Height	280 mm	300 mm	400 mm
Net Weight	2,5 kg	3 kg	5 kg
Price	399:-	499:-	950:-

### CP85031

### Air-hydraulic Jack, 30 t

- High Lifting
- · Air powered piston
- Includes 2 extensions for higher lifting Stored on handle for transport
- · Anti dust seals for high durability
- · Convenient joystick controls
- Cylinder mounted carrying handle
- 1.3 m / long handle bar (1 piece handle) allows easy access to controls when fully positioned under vehicle
- Handle bar locks in 3 positions: 45°, 90° & 180°
- Large & soft rubber wheels
- · Maximum height: 772 mm at 30 tons





# **WORKSHOP EQUIPMENT**

### **CP Workshop Presses**

### 20t-100t pressing power

- · 2 holes in each foot to fix in the floor
- · Steel frame
- · 2 step stroke system
- · Large gauge measuring short and metric tons
- · Delivered with 2 V blocks
- · Easy to use handle with rubber grip
- Delivered with a quick chuck and 8 punches



### **HR8113**

### Hose Reel

- 16m hose
- · BSP thread
- 13mm inner diameter
- · Weight 10.7 kg
- Air connection 1/2"



3900:-Art.-Nr.: 8940171999



### Hi There,

You want to be regularly informed about new products and events?

Sign up to our CP email newsletter at: www.cp.com/en/tools/expert-corner/subscribe



### **CP FRL Unit:**

### Take control of your operating costs

Extends the life of your air tools and reduces the energy demand. Tools are automatically set to the optimum oil supply is controlled and the filter provides protection against dirt and water

### CLEAN AIR, FULL POWER.

FRL Unit- 1/2" Connection BSP

2140:-Art.-Nr.: 8940168480

FRL Stand

1060:-Art.-Nr.: 6158120450



# Our complete Assortment Online: www.cp.com/nordic Online Catalog Pneumatic Tools Online workshop equipment catalogue CP accessories Technical documentation CP sales and dealer contacts



At Chicago Pneumatic, we have a passion for performance and long-lasting partnerships. Since 1901, we have been committed to reliability based on technology and trust.

People: Passion. Performance.

# **CORDLESS TOOLS**

### **COMFORT. ERGONOMICS. POWER.**





### **CP8854**

### **Cordless Impact Wrench 1/2"**

- The performance of a Twin-hammer with the advantages of an advanced electric motor
- Offers high flexibility and protects against arm injuries.
- No more over tightening the bolts thanks a torque cut-off when tightening
- · 2-stage tightening



Model	CP8854
Article no.	8941088540
Square drive	1/2"
Max Torque (Reverse)	1.050 Nm
Battery pack	Lithium-ion
Noise level	91 db(A)
Net weight	2,5 kg + 0,49 kg Battery
Vibration	1,5 m/s <sup>2</sup>



### Cordless high-torque screwdriver

- · Lightweight construction thanks to the compact CP battery
- · 250 cycles before changing the battery
- · Powerful torque thanks to special gears
- The gearbox of the CP86 allows high-precision tightening with constant repeatability
- · Intuitive large OLED display

INTERESTED?
ASK US FOR A QOUTE!

Model	CP8613
Article no.	6151570000
Square drive	3/4"
Max Torque (Reverse)	1.300 Nm
Battery pack	Li ion, 36V, 2,5 Ah
Noise level	< 72 db(A)
Net weight	4,5 kg + 0,8 kg Battery
Vibration	< 2.5 m/s <sup>2</sup>



You want to be regularly informed about new products and events?
Sign up to our CP email newsletter at:
www.cp.com/en/tools/expert-corner/subscribe